

## TRIAC AT

The new TRIAC AT is an intelligent yet robust hot air tool for welding and shrinking plastic. It is designed for the needs of even the most demanding professional. The TRIAC AT incorporates an ergonomic design, secure handling and a modern look.



reddot design award  
honourable mention 2012



- Everything easily:  
Intuitive handling with proven «e-Drive» operating unit.
- Everything in view:  
Clearly visible information on the large «e-Drive» display.
- Everything automatically:  
The set temperature reaches its level automatically, voltage fluctuations are compensated.
- Everything under control:  
The temperature measurement probe guarantees a precise temperature.
- Everything flexible:  
The air volume can be adjusted independently.

## SPECIFICATIONS

### 230

Voltage	V~	230
Power consumption	W	1600
Temperature	°C	40 – 700
Air flow (20°C)	l/min	120 – 240
Size (L x ø)	mm	335 x 90, handle □ 56
Weight	kg	1 (without 3 m cord)

Marking of conformity



Protection class II



Article Number



141.314

### 120

Voltage	V~	120
---------	----	-----



Plastic Welding > Hand tools > TRIAC AT

---

Power consumption	W	1600
Temperature	°C	40 – 700
Air flow (20°C)	l/min	120 – 240
Size (L x ø)	mm	335 × 90, handle □ 56
Weight	kg	1 (without 3 m cord)
Marking of conformity		
Protection class II		
Article Number		141.316

---

100

Voltage	V~	100
Power consumption	W	1400
Temperature	°C	40 – 700
Air flow (20°C)	l/min	120 – 240
Size (L x ø)	mm	335 × 90, handle □ 56
Weight	kg	1 (without 3 m cord)
Marking of conformity		
Protection class II		
Article Number		141.319

## ACCESSORIES



Tacking nozzle push-fit on tubular nozzle ø 5 mm

106.996 - Tacking nozzle, push-fit on tubular nozzle Ø 5mm



Tubular nozzle ø 5 mm push-fit on TRIAC PID / TRIAC S / TRIAC AT

100.303 - Tubular nozzle Ø 5 mm, push-fit



Speed welding nozzle 3, 4, 5 mm push-fit on tubular nozzle Ø 5 mm

106.989 - Speed welding nozzle 3 mm, push-fit on tubular nozzle Ø 5 mm

106.990 - Speed welding nozzle 4 mm push-fit, on tubular nozzle Ø 5 mm


106.991 - Speed welding nozzle 5 mm, push-fit on tubular nozzle Ø 5 mm



Speed welding nozzle 5.7, 7 mm push-fit on tubular nozzle Ø 5 mm

106.992 - Speed welding nozzle 5.7 mm, push-fit on tubular nozzle Ø 5 mm

106.993 - Speed welding nozzle 7 mm, push-fit on tubular nozzle Ø 5 mm



Angled nozzle 20 mm, 90° push-fit on TRIAC PID / TRIAC S / TRIAC AT

107.124 - Angled nozzle 20 mm, 90°, push-fit



Angled nozzle 20 mm, 60° push-fit on TRIAC PID / TRIAC S / TRIAC AT

107.125 - Angled nozzle 20 mm, 60°, push-fit



Wide slot nozzle 40 mm, push-fit on TRIAC PID, TRIAC S, TRIAC AT

107.132 - Wide slot nozzle 40 mm, push-fit

## Plastic Welding &gt; Hand tools &gt; TRIAC AT



Wide slot nozzle 40 mm, 60° bent push-fit on TRIAC PID / TRIAC S / TRIAC AT  
107.130 - Wide slot nozzle 40 mm, 60° bent, push-fit



Wide slot nozzle 40 mm, perforated push-fit on TRIAC PID / TRIAC S / TRIAC AT  
107.133 - Wide slot nozzle 40 mm, perforated, push-fit



Wide slot nozzle 30 mm, push-fit for TRIAC AT  
128.535 - 45° angle



Wide slot nozzle 60 mm push-fit on TRIAC PID / TRIAC S / TRIAC AT  
107.129 - Wide slot nozzle 60 mm, push-fit




Wide slot nozzle 80 mm push-fit on TRIAC PID / TRIAC S / TRIAC AT  
107.131 - Wide slot nozzle 80 mm, push-fit



Wide slot nozzle  $\varnothing$  20 mm, push-fit on TRIAC PID, TRIAC S / TRIAC AT  
107.123 - Wide slot nozzle 20 mm, push-fit



Extension nozzle  $\square$  5 mm  
106.982 - 150 mm



Sieve reflector 12 x 10 mm push-fit on tubular nozzle  $\varnothing$  5mm  
107.324 - Sieve reflector 12 x 10 mm, push-fit on tubular nozzle  $\varnothing$  5mm

## Plastic Welding &gt; Hand tools &gt; TRIAC AT



Spoon reflector 27 x 35mm push-fit on TRIAC PID / TRIAC S / TRIAC AT

107.307 - Spoon reflector 27 x 35 mm, push-fit



Heating element for TRIAC AT

142.637 - 230 V / 1550 W

142.638 - 120 V / 1550 W

142.639 - 100 V / 1350 W



Leister cutter with four spare blades

137.855 -