

MAK Fastener Specialists Pty Ltd.,
Unit 4, 11 Trevi Crescent,
Tullamarine, VIC 3043
Australia.

Web Site: www.makfasteners.com.au

Tel.: +61 (0)3 9078 9119

Fax: +61 (0)3 9078 9119

E-mail: Sales@MakFasteners.com.au



**MAK
FASTENER
SPECIALISTS
pty LTD**

Fasteners for Roofing, Cladding
and General Construction

Product Group 12

PVC Tapes

Description

PVC foam sealant tapes are manufactured from expanded PVC in a range of densities. They are essentially closed cell structures coated with a pressure sensitive acrylic adhesive and require 30% compression to create a water seal.



Typical Applications

- Roofing and cladding seals
- Cold room panels and cold bridging
- Sealing partition walls
- Heating and ventilation
- Roof lights, access doors and gutter joints
- Profiled sheeting
- Prefabricated tanks

MAK Fastener Specialists Pty Ltd.,
 Unit 4, 11 Trevi Crescent,
 Tullamarine, VIC 3043
 Australia.

Web Site: www.makfasteners.com.au

Tel.: +61 (0)3 9078 9119

Fax: +61 (0)3 9078 9119

E-mail: Sales@MakFasteners.com.au



MAK
FASTENER
SPECIALISTS
 pty LTD

Fasteners for Roofing, Cladding
 and General Construction

Product Group 12

PVC Tapes

Technical Information

	20 Series	25 Series	50 Series
Adhesive	Acrylic	Acrylic	Acrylic
Colours	Black/White	Black/Grey	Black/Grey
Thicknesses (mm)	Black: 3, 4.5, 6 White: 3, 6	Black: 1.5, 3, 4.5, 6, 7.5, 9, 10.5, 12 Grey: 1.5, 3, 4.5, 6	Black: 1.5, 3, 4.5, 6 Grey: 0.8, 1.5, 2.5, 3, 4.5, 6
Density (kg/m ³)	115	130	220
Shore Hardness (00 Scale)	30	35	50
Force to Compress (Ncm ⁻²)	2.7	3.2	6.1
Tensile strength (kPa)	300	460	670
Elongation at Break (%)	>160	>155	>180
Peel Adhesion (N/25mm)	5	5	5
Service temperature	-30°C to +70°C	-30°C to +70°C	-30°C to +70°C
Application temperature	+10°C to +40°C	+10°C to +40°C	+10°C to +40°C
UV Resistance	Excellent	Excellent	Excellent
Fungi resistance	Excellent	Excellent	Excellent
Weather resistance	Excellent	Excellent	Excellent
Shelf life	2 Years	2 Years	2 Years